


## SECURUS CAT6 OUTDOOR DOUBLE COATED CABLE



### Key Features

- Electrolytic Grade Copper.
- Standard 24 AWG Gauge.
- Sequential Meter Marking.
- 305 Meters Wooden Drum.

Parameter	Details
Product	CAT6 OUTDOOR DOUBLE COATED CABLE
Product Range	Utility Range
Make	<b>SECURUS</b>
Conductor	Solid Bare Electrolytic Grade Copper
Nominal Conductor Diameter	24 AWG (0.510 ± 0.015 mm)
Insulation	Polyethylene (HDPE)
Pairing	Twisted Into Two Core
No. Of Pair	4, Each Twisted Pair
Color Code	
Pair #1	Orange-White & Orange
Pair #2	Brown-White & Brown
Pair #3	Blue-White & Blue
Pair #4	Green-White & Green
Inner Sheath Material	PVC
Inner Sheath Color	Grey
Outer Sheath Material	LDPE
Outer Sheath Color	Black

Parameter	Details
Approximate OD	6.70 ± 0.50mm
Rip Cord	Yes
Sequential Marking	Meter Marking
Cross Filler	HDPE
DC	93.5Ω / 100 Meters
Resistance Unbalance	5% Max
Mutual Capacitance	5.6nf / 100 Meters (Max)
NVP	69%
Impedance	100Ω (± 15Ω)
Worst Cable Skew	45ns / 100 Meters
Installation Temperature	0°C ~ +50°C
Storage Temperature	-20°C ~ +75°C
Operating Temperature	-20°C ~ +60°C
Packing Length	305 Meters
Packing Type	Wooden Drum Packing
Certifications	CE, FCC, ROHS