



**SECURUS PROPRIETARY MOBILE APP**

**5in1  
DVR**



## **SECURUS SS-0804ASL-AHD-M1**

8 Channels 1080N Standalone DVR with HDMI

A Professional 8 Channels H.264 Hardware Compression Standalone. Supports Mobile Viewing on iPhone and Android Mobiles via **REYES** Application. You can format HDD and control entire device using the mobile application. It has one of the easiest Playback and Backup modes. Hence, the Device is very User Friendly.

**SECURUS RANGE  
01-05-2016**





| <b>Parameter</b>            | <b>Details</b>                             |
|-----------------------------|--|
| <b>Model</b>                | SS-0804ASL-AHD-M1                          |
| <b>Make</b>                 | <b>SECURUS</b>                             |
| <b>User Interface</b>       | Graphic User Interface (OSD)               |
| <b>Operating System</b>     | Embedded Linux                             |
| <b>Operation Mode</b>       | Preview, Record, Playback, Backup, Network |
| <b>Password Security</b>    | Multi-level User Management                |
| <b>Audio Input</b>          | 4 in, RCA                                  |
| <b>Video Input</b>          | 8 in, BNC                                  |
| <b>HDMI Output</b>          | Supports                                   |
| <b>VGA output</b>           | Supports                                   |
| <b>CVBS main output</b>     | N.A.                                       |
| <b>Audio output</b>         | 1 out, RCA                                 |
| <b>Display</b>              | 1/4 /6/8/9 optional                        |
| <b>Video standard</b>       | PAL/NTSC                                   |
| <b>Loop</b>                 | N.A.                                       |
| <b>Spot output</b>          | N.A.                                       |
| <b>Video compression</b>    | H.264                                      |
| <b>Recording frame rate</b> | 1-25FPS                                    |
| <b>Video frame rate</b>     | 1-25FPS                                    |

| <b>Parameter</b>            | <b>Details</b>   |
|-----------------------------|--|
| <b>Video bit rate</b>       | WCIF(CIF) :512-1024kbps,WD1(D1) :<br>1024-2048kbps,720P:1536-3072kbps,<br>1080N :1728-3456kbps<br>1080P :4608-6144kbps |
| <b>Stream Type</b>          | Video & Audio/Video  |
| <b>Audio compression</b>    | ADPCM  |
| <b>Recording mode</b>       | Always/Schedule/Alarm<br>recording/Motion detection recording  |
| <b>Video search</b>         | Time/Channel/Event   |
| <b>Audio bit rate</b>       | 8—32kbps   |
| <b>Dual-stream</b>          | Supports   |
| <b>Mobile Monitoring</b>    | "REyes" Application for Android / iPhone<br>iPad   |
| <b>Recording resolution</b> | 8CH AHD/TVI/CVI/960H/IPC/<br>1080N/720P recording & 4Ch Playback<br>4CH IPC 1080P recording & 4Ch<br>Playback          |
| <b>Preview resolution</b>   | 1080P:1920x1080,1080N:960x1080,<br>720P:1280x720,WD1:960x576,<br>D1:704x576, CIF:352x288                               |
| <b>Recording Playback</b>   | 1-4 Channel optional   |
| <b>HDD Port</b>             | 1 pieces SATA  |
| <b>HDD Maximum Capacity</b> | 6TB for each Sata connector  |
| <b>Voice talk</b>           | N.A.   |
| <b>Record mode</b>          | Audio & Video recording simultaneously   |

| <b>Parameter</b>             | <b>Details</b>                       |
|------------------------------|--------------------------------------|
| <b>DDNS Server</b>           | www.securusddns.com,www.uviewcan.net |
| <b>Serial Port</b>           | 1 RS-485 Serial port                 |
| <b>Network Protocol</b>      | Supports IE/PPPoE/DDNS/              |
| <b>Network</b>               | 1 RJ45 10M/100M                      |
| <b>E-Sata Connector</b>      | N.A.                                 |
| <b>USB Connector</b>         | 2 USB                                |
| <b>Firmware update</b>       | Support USB update/Network update    |
| <b>Alarm input</b>           | N.A.                                 |
| <b>Alarm output</b>          | N.A.                                 |
| <b>Power supply</b>          | DC 12V 2A                            |
| <b>Operation Temperature</b> | -10°C-- +55°C                        |
| <b>Operation Humidity</b>    | 10%--90%                             |
| <b>Chassis</b>               | MINI 1U                              |
| <b>Dimension</b>             | 255mm (L)×236mm (W)×44mm (H)         |
| <b>Weight(without HDD)</b>   | ≤1.5Kg                               |

## REyes Mobile Application



**Android**



**iPhone**

© K.M. Electronic Cables Pvt. Ltd. - Ahmedabad. All Rights Reserved.  
Specifications are subject to change without prior notice.