

Product Technical Specifications Utility Range

## SS-20L2T-TPHD-M2.4 2.4 MP HD-TVI IR METAL BULLET CAMERA



**Key Features** 

- 2.4 Megapixel.
- 18 SMD IR LED.
- HD-TVI Technology.
- 12V DC Power Supply.
- 3.6mm/4.0mm/6.0mm HD Lens.



Parameter	Details
Model	SS-20L2T-TPHD-M2.4
Make	SECURUS
Product Range	Utility Range
Image Sensor	1/2.7" 2.4 Megapixel Image Sensor
Product Range	Utility Range
TV System	PAL/NTSC
Video Standard	Compliance with HD-TVI
Effective Pixel	1984 x 1225 Pixels
Video Frame Rate	1984 x 1225 Pixels @ 25FPS
Video Output	1 x BNC Video Out
Video Output Format	HD-TVI, CVI, AHD, CVBS
Lens Mount	3.6mm/4.0mm/6.0mm HD Lens
Day/Night	Auto(ICR)/Color/BW
BLC	Auto
AWB	Auto
IR Distance	20 ~ 40 Meters
LED Wavelength	18 SMD IR LED
Minimum Illumination	0.01 Lux/ F1.2 (AGC ON)

SECURUS HD-TVI SERIES CAMERA RANGE 16-01-2023

© K. M. Electronic Cables Pvt. Ltd. - Ahmedabad. All Rights Reserved.

Specifications are subject to change without prior notice.



Parameter	Details
Noise Reduction	2D/3D
Synchronization	Internal
Electronic Shutter Speed	1/25 - 1/50,000 seconds
Transmission	500 Meters @ 75-3 Coaxial Cable
Power Supply	12V DC ±10%
Operation Temperature	-10 to 85 deg. C (Humidity: 95% max)
IP Rating	IP67 (METAL BODY)