



**PURPLE**

**HD-TVI**

## **SECURUS SS-20L2T-TPHD-M5**

5.0 Megapixel HD-TVI IR Metal Bullet Camera for Outdoor use.

SS-20L2T-TPHD-M5 is 5.0 Megapixel IR Bullet Camera. HD-TVI Cameras are part of the Latest Revolution in Surveillance Industry. HD-TVI Cameras deliver 5.0 Megapixel resolution over Normal Co-Axial Cables. It supports a transmission distance of up to 500 Meters. Securus HD-TVI Cameras deliver amazing image in both Day and Night Modes.

SECURUS HD-TVI SERIES CAMERA RANGE

**01-10-2019**

**5.0MP**

**HD-TVI**

**3.6MM**

**SMART  
IR LED**

**20  
METERS**

| Parameter                       | Details                              |
|---------------------------------|--------------------------------------|
| <b>Model</b>                    | SS-20L2T-TPHD-M5                     |
| <b>Make</b>                     | <b>SECURUS</b>                       |
| <b>Image Sensor</b>             | 1/2.5" 5.0 Megapixel Image Sensor    |
| <b>TV System</b>                | PAL/NTSC                             |
| <b>Video Standard</b>           | Compliance with HD-TVI               |
| <b>Effective Pixel</b>          | 2608 x 1952 Pixels                   |
| <b>Video Frame Rate</b>         | 2608 x 1952 Pixels @ 20FPS           |
| <b>Video Output</b>             | 1 x BNC Video Out                    |
| <b>Video Output Format</b>      | HD-TVI, CVI, AHD, CVBS               |
| <b>Lens Mount</b>               | 3.6mm 5.0MP HD Lens                  |
| <b>Day/Night</b>                | Auto(ICR)/Color/BW                   |
| <b>BLC</b>                      | Auto                                 |
| <b>AWB</b>                      | Auto                                 |
| <b>IR Distance</b>              | 20 Meters                            |
| <b>LED Wavelength</b>           | 18 SMD IR LED                        |
| <b>Minimum Illumination</b>     | 0.01 Lux/ F1.2 (AGC ON)              |
| <b>Noise Reduction</b>          | 2D/3D                                |
| <b>Synchronization</b>          | Internal                             |
| <b>Electronic Shutter Speed</b> | 1/25 - 1/50,000 seconds              |
| <b>Transmission</b>             | 500 Meters @ 75-3 Coaxial Cable      |
| <b>Power Supply</b>             | 12V DC ±10%                          |
| <b>Operation Temperature</b>    | -10 to 85 deg. C (Humidity: 95% max) |
| <b>IP Rating</b>                | IP67 (METAL BODY)                    |