



AHD

Analogue High Definition

TURBO MODE

Analogue + IP Camera + AHD

1080N



SECURUS SS-3216V-AHD-M1

32 Channels AHD DVR Standalone with 2 SATA

A Professional 32 Channels AHD H.264 Hardware Compression Standalone. Supports Mobile Viewing on iPhone and Android Mobiles. It has Turbo Mode which means that you can connect Analogue Cameras, IP Cameras and AHD Cameras on the same device. It has one of the easiest Playback and Backup modes. The Device GUI is very User Friendly.

SECURUS AHD DVR
RANGE 01-03-2015





Parameter	Details
Model	SS-3216V-AHD-M1
Make	SECURUS
User Interface	Graphic User Interface (GUI)
Operating System	Embedded Linux
Video Compression	H.264 (High Profile)
Video Input	32*BNC (Support Coaxitron)
Video Output	N.A.
VGA Output	1*VGA (MAX:1080P)
HDMI Output	1*HDMI (MAX:1080P)
Display Resolution	AHD: 1080P; 1080N; 720P
Audio Compression	G.711A
Intercom	Support
Audio Input	-8Db 22K Ω , 16xRCA
Audio Output	-8Db 03K Ω , 1xRCA
Recording Mode	Manual/Alarm/Motion detection/Timing
Recording Resolutions	1080P, 1080N, 720P, 960H, D1, CIF
Recording Parameters	MAX: 32 x 1080N @ 25 FPS
Recording Playback	16 Channel




Parameter	Details
HDD Port	2 x SATA (Max- 6TB Each)
Backup Modes	Network, USB, SATA
Storage mode	HDD Storage, Network Storage
Ethernet Port	1*10/100/1000Mbps,Ethernet Port,RJ45 port
Network Protocol	IPv4,PPPoE,3G,DDNS,NTP, ARSP, SMTP, P2P Cloud, UPnP
ONVIF Protocol	Compliant
DDNS Service	FREE DDNS: www.securusddns.com
P2P Cloud Service	Available
PTZ Control	1*RS485,Support for multiple,PTZ protocol
USB Connectors	2 USB Ports
Alarm Input	16 Input
Alarm Output	4 Output
Power Supply	DC12 Volts 2 Amperes
Power Consumption	≤10W (No HDD)
Dimensions	440mm(L)* 290mm(W)* 50mm(H)
Weight	Around 3KG (No HDD)
Temperature	0 °C - + 55 °C
Inquire mode	Inquire by Time/Calendar/Event/Channel
Environmental Humidity	10% ~ 90% RH

Parameter	Details
Encode	32*1080N@15fps;24*1080N;16*1080N
Decode	Network, USB HDD, USB DVD-Writer
Multi-mode	Analog:32*1080N@15fps; 24*1080N;16*1080N Hybird:8*1080N(analog)+8*960P(network) IP: 32*1080P/16*3M/8*5M

RMEYE Mobile Application



Android



iPhone