


SS-N04EP-E2 | 4 Ports 10/100 POE + 2 Ports 10/100 Uplink

Key Features

- 4 x 100 Mbps Ethernet Ports + 2 x 100 Mbps up-link Ports
- Supports VLAN/CCTV Mode to POE up-to 250 Meters
- Can supply Max 30W Power on Each Port
- Max Power Budget of 60W
- Compliance with IEEE802.3 af/at Standards
- Supports IEEE802.3x Full-Duplex Flow Control
- Supports Auto MDI/MDIX
- Excellent Lightning Protection up-to 6KV
- Easy to Install and Operate

Parameter	Details
Model	SS-N04EP-E2
Make	SECURUS
Network Ports	4 Ethernet Ports : 10/100 Mbps 2 Up-link Ports: 10/100 Mbps
Transmission Distance	4 POE Ethernet Ports : 100 Mtrs @ 100 Mbps; 250Mtrs @ 10Mbps 2 Up-link Ports : 100 Meters
Transmission Media	Cat5e/Cat6 Standard UTP Cable
POE Standard	IEEE802.3 af/at Standard
POE Power Supply Method	End-Span Method
POE Power Supply Watt	Each Port ≤30W, Total Power 60W
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3az, IEEE802.3z
Swap Mode	Store & Forward
Data Caching Mechanism	448K
MAC Address List	2 K
Reset Button	Available
VLAN Switch	Available

Parameter	Details
Power Supply Mode	Power Adaptor
Voltage Range	DC48V ~ 56V
Power Consumption	Device: <5W ; Adaptor: <60W
Working Temperature	-10°C ~ 60°C
Storage Temperature	-40°C ~ 75°C
Humidity	0 ~ 95%
Dimensions (L x W x H)	160mm x 94mm x 28mm
Color (Chasis)	Black
Weight	425 Grams
Mean Time Between Failures (MTBF)	>50000 Hours