

SS-N08EP-E2 | 8 Ports 10/100 POE + 2 Ports 10/100 Uplink



Key Features

- 8 x 100 Mbps Ethernet Ports + 2 x 100 Mbps up-link Ports
- Supports VLAN/CCTV Mode to POEup-to 250 Meters
- Can supply Max 30W Power on Each Port
- Max Power Budget of 120W
- Compliance with IEEE802.3 af/at Standards
- Supports IEEE802.3x Full-Duplex Flow Control
- Supports Auto MDI/MDIX
- Excellent Lightning Protection up-to 4KV
- "E" Mode : 1-8 port supports 250M meters long distance power supply
- "I" Mode : Isolating ports 1-8 from each other, restrain network storms effectively and improve network performance
- "Q" Mode : Prioritize the identified video data to make video transmission smoother
- "P" Mode : Automatic detection power of port, power off and restart the device if find dead machine
- Easy to Install and Operate

Parameter	Details
Model	SS-N08EP-E2
Make	SECURUS
Network Ports	8 Ethernet Ports : 10/100 Mbps 2 Up-link Ports: 10/100 Mbps
Transmission Distance	8 POE Ethernet Ports : 100 Mtrs @ 100 Mbps; 250 Mtrs @ 10 Mbps 2 Up-link Ports : 100 Meters
Transmission Media	Cat5e/Cat6 Standard UTP Cable
POE Standard	IEEE802.3 af/at Standard
POE Power Supply Method	End-Span Method
POE Power Supply Watt	Each Port ≤30W, Total Power 120W
Network Standard	IEEE802.3i, IEEE802.3u, IEEE802.3x, IEEE802.3af, IEEE802.3at
Swap Mode	Store & Forward
Data Caching Mechanism	1M
MAC Address List	2 K

Parameter	Details
Power Supply Mode	Power Adaptor
Voltage Range	DC48V ~ 56V
Power Consumption	Device: <5W ; Adaptor: <120W
Working Temperature	0°C ~ 55°C
Storage Temperature	-40°C ~ 70°C
Humidity	10 ~ 90%
Dimensions (L x W x H)	184mm x 94mm x 27mm
Color (Chasis)	Black
Weight	500 Grams
Mean Time Between Failures (MTBF)	>50000 Hours