

SS-N08EP-G2 | 8 Ports 10/100 POE + 2 Ports 10/100/1000 Uplink



Key Features

- 8 x 100 Mbps Ethernet Ports + 2 x 1000 Mbps up-link Ports
- Supports VLAN/CCTV Mode to POE up-to 250 Meters
- Can supply Max 30W Power on Each Port
- Max Power Budget of 120W
- Compliance with IEEE802.3 af/at Standards
- Supports IEEE802.3x Full-Duplex Flow Control
- Supports Auto MDI/MDIX
- Excellent Lightning Protection up-to 6KV
- Easy to Install and Operate

Parameter	Details
Model	SS-N08EP-G2
Make	SECURUS
Network Ports	8 Ethernet Ports : 10/100 Mbps 2 Up-link Ports: 10/100/1000 Mbps
Transmission Distance	8 POE Ethernet Ports : 100 Mtrs @ 100 Mbps; 250 Mtrs @ 10 Mbps 2 Up-link Ports : 100 Meters
Transmission Media	Cat5e/Cat6 Standard UTP Cable
POE Standard	IEEE802.3 af/at Standard
POE Power Supply Method	End-Span Method
POE Power Supply Watt	Each Port ≤30W, Total Power 120W
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3az, IEEE802.3z
Swap Mode	Store & Forward
Data Caching Mechanism	1 M
MAC Address List	2 K
Reset Button	Available
VLAN Switch	Available
Bandwidth	5.6 Gbps
Frames filter and transfer rate	10M port maximum 14,800pps, 100M port maximum 148,800pps

Parameter	Details
Communication Protocols	IPv4 and IPv6 Compatible
Power Supply Mode	Power Adaptor
Voltage Range	DC48V ~ 56V
Power Consumption	Device: <5W ; Adaptor: <120W
Working Temperature	-10°C ~ +60°C
Storage Temperature	-40°C ~ +75°C
Humidity	0 ~ 95%
Dimensions (L x W x H)	220mm x 105mm x 28mm
Color (Chasis)	Black
Weight	612 Grams
Mean Time Between Failures (MTBF)	>50000 Hours
Certifications	CE, FCC, RoHS