

SS-N08EP-G2 | 8 Ports 10/100 POE + 2 Ports 10/100/1000 Uplink



Key Features

- **8 x 100 Mbps Ethernet Ports + 2 x 1000 Mbps up-link Ports**
- **Supports VLAN/CCTV Mode to POE up-to 250 Meters**
- **Can supply Max 30W Power on Each Port**
- **Max Power Budget of 120W**
- **Compliance with IEEE802.3 af/at Standards**
- **Supports IEEE802.3x Full-Duplex Flow Control**
- **Supports Auto MDI/MDIX**
- **Excellent Lightning Protection up-to 4KV**
- **Easy to Install and Operate**

Specifications

Parameter	Details
Model	SS-N08EP-G2
Make	SECURUS
Network Ports	8 Ethernet Ports : 10/100 Mbps 2 Up-link Ports: 10/100/1000 Mbps
Transmission Distance	8 POE Ethernet Ports : 100 Mtrs @ 100 Mbps; 250 Mtrs @ 10 Mbps 2 Up-link Ports : 100 Meters
Transmission Media	Cat5e/Cat6 Standard UTP Cable
POE Standard	IEEE802.3 af/at Standard
POE Power Supply Method	End-Span Method
POE Power Supply Watt	Each Port \leq30W, Total Power 120W
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3az, IEEE802.3z
Swap Mode	Store & Forward
Data Caching Mechanism	1 M
MAC Address List	2 K
Reset Button	Available
VLAN Switch	Available

Parameter	Details
Power Supply Mode	Power Adaptor
Voltage Range	DC48V ~ 56V
Power Consumption	Device: <5W ; Adaptor: <120W
Working Temperature	0° C ~ 55° C
Storage Temperature	-40° C ~ 70° C
Humidity	0 ~ 95%
Dimensions (L x W x H)	220mm x 105mm x 28mm
Color (Chasis)	Black
Weight	612 Grams
Mean Time Between Failures (MTBF)	>50000 Hours