



NETWORK VIDEO RECORDER (NVR)
SUPPORTS 32 CH 1080P IP CAMERAS



SECURUS PROPRIETARY MOBILE APP



SECURUS SS-N32-H2-M1 NVR

32 Channels 1080P Standalone NVR with HDMI

A Professional 32 Channels H.264 Hardware Compression Standalone. Supports Mobile Viewing on iPhone and Android Mobiles via **REYES** Application. You can format HDD and control entire device using the mobile application. It has one of the easiest Playback and Backup modes.

SECURUS NVR RANGE
01-05-2016



Parameter	Details
Model	SS-N32-H2-M1
Make	SECURUS
User Interface	Graphic User Interface (GUI)
Operating System	Embedded Linux
Operation Mode	Preview, Record, Playback, Backup, Network
Password Security	Multi-level User Management
ONVIF	Support
Video Input	32 CH 1080P IPC
HDMI Output	Supports
VGA output	Supports
CVBS main output	1CH, BNC connector
Audio output	1CH,RCA connector
Display	1/4/6/8/9/10/13/16/24 /32optional
Video standard	PAL/NTSC
Video compression	H.264
Display frame rate	PAL: 800 FPS (32 x 25 fps). NTSC: 960 FPS (32 x 30 fps)
Recording frame rate	PAL: 800 FPS (32 x 25 fps) NTSC: 960 FPS (32 x 30 fps)
Video encoding resolution	PAL: 1080P (1920 x 1080 Pixels) NTSC: 1080P (1920 x 1080 Pixels)
Video frame rate	PAL: 1-25FPS NTSC:1-30FPS



Parameter	Details
Video bit rate	1536kbps-3072kbps;
Stream Type	Video & Audio/Video
Audio compression	ADPCM
Recording mode	Always/Schedule/Alarm recording/Motion detection recording
Video search	Time/Channel/Event
Audio bit rate	8—32kbps
Dual-stream	Supports
Mobile Monitoring	"REyes" Application for Android and iPhone
Recording resolution	24 CH 1080P Recording + 4 CH realtime Playback
HDD Port	2 pieces SATA
HDD Maximum Capacity	4TB for each Sata connector
Voice talk	Support, 1CH BNC line in/1CH RCA audio out.
Record mode	Audio & Video recording simultaneously
Remote control	Supports
Network protocol	Supports IE/PPPoE/DDNS
DDNS Server	www.securusddns.com
Digital Zoom	Live Playback & Mobile
Network	1 RJ45 10M/100M/1000M
USB Connector	2 USB 2.0

Parameter	Details
Firmware update	Support USB update/Network update
Alarm input	8 Inputs
Alarm output	1 Outputs
Power supply	NVR: DC 12V 5A
Operation Temperature	-10°C--55°C
Operation Humidity	10%--90%
Chassis	Standard 1.5U
Dimension	321mm (W)×405mm (D)×65mm (H)
Weight(without HDD)	≤3.0Kg

REyes Mobile Application



Android



iPhone