


SS-N8032RV-H4-M5 | AI Network Video Recorder



Key Features

- Playback and Backup modes.
- ONVIF Support.
- Face Detection.
- RMEye Pro Application.
- Video Compression H.265AI/H.265+.



Parameter	Details
Model	SS-N8032RV-H4-M5
Make	SECURUS
User Interface	Graphic User Interface (GUI)
Operating System	Embedded Linux
Operation Mode	Preview, Record, Playback, Backup, Network, Smart Search
Playback Mode	Common Playback, Smart Search
Password Security	Multi-level User Management
ONVIF	Support
Video Input	32ch 5M/32ch1080P/8ch4K
HDMI Output	Supports (Max : 4K)
VGA Output	Supports (Max : 1080P)
CVBS main output	N.A.
Audio Input	1 Ch
Audio output	1 Ch, RCA connector
Display	1/4/6/8/9/10/13/16/25/32 optional
Video standard	PAL/NTSC
Video compression	H.265AI/H.265+/H.265/H.264+/H.264
Intelligent Functions	Trip Wire, Face Detection
Video encoding resolution	12MP; 8MP; 5MP; 4MP; 3MP; 1080P

Parameter	Details
Video frame rate	PAL: 1-25 FPS NTSC: 1-30FPS
Video bit rate	1536kbps-3072kbps
Stream Type	Video & Audio/Video
Audio compression	G.711a
Recording mode	Always/Schedule/Alarm/Recording/Motion Detection Recording
Video search	Time/Channel/Event
Display Zoom	Live Playback & Mobile
Audio bit rate	8-32kbps
Dual-stream	Supports
Mobile Monitoring	"RMEeye Pro" Application for Android And iPhone
Recording resolution	32 CH Realtime Recording
HDD Port	4 SATA
HDD Maximum Capacity	12TB for each Sata connector
Voice talk	Support, 1CH BNC line in/1CH RCA Audio out.
Record mode	Audio & Video recording simultaneously
Remote control	Supports
Network protocol	Supports IE/PPPoE/DDNS
Multiple IP Network Configuration	Supported
Network Bandwidth	240Mbps Incoming / 240Mbps Outgoing

Parameter	Details
DDNS Server	www.securusddns.com
Network	1 RJ45 10M/100M/1000M
NVR to NVR Cascading	Remote, Local, Viewing, Recording
IPC firmware update	Supported
USB Connector	2 x USB2.0, 1 x USB3.0
Firmware update	Support USB update/Network update
Alarm input	16
Alarm output	4
Power supply	NVR: DC 12V 6A
Operation Temperature	-10°C-- +55°C
Operation Humidity	10%--90%
Chassis	Standard 1.5U
Dimension	400.5mm (W) × 440mm (L) × 60mm (H)
Weight(without HDD)	≤1.0Kg
Certifications	CE, FCC, RoHS, BIS.

RMEye Pro Mobile Application



Android

iPhone