




SMARTEXIR
TECHNOLOGY

IN BUILT AUDIO

SECURUS SS-NC15DXLP-SEF-M2(S)

2.0 MP AI Network Dome Camera with Built in Audio

Securus Latest Range of AI Cameras with Face Detection & Face Recognition Feature. 2.0 Megapixel Network Bullet Camera. It is **ONVIF** Compliant which means that it will work on all major DVR. It supports PoE Function. It comes with a weather-proof connector which is ideal for Outdoor Applications.

SECURUS AI Network Camera Range
01-01-2021

H.265AI

AUDIO

AI


POE

IP67

WDR



**FACE
RECOGNITION**



Parameter	Details
Model	SS-NC15DXLP-SEF-M2(S)
Make	SECURUS
Image Sensor	1/2.7" Progressive Scan CMOS
Image Pixels	1920 x 1080 Pixels (2.0 MP)
Minimum Illumination	0.01Lux @ (F1.2,AGC ON),0Lux with IR
Day/Night	Auto (ICR) / Color / Black & White
WDR (Wide Dynamic Range)	≥120db
IR LED	2Pcs IR LED
IR LED Technology	SmartEXIR [®] Technology
IR Distance	20 Meters
Shutter Type	Manual/Auto
Shutter Speed	1/25s ~ 1/100000s
Lens Mount	3.6 Megapixel Lens
Lens Type	Board Lens
Network Interface	10/100 MBPS RJ45 Connector
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
Electronic Shutter Speed	Manual/Auto (1/25 ~ 1/100000 S)
ONVIF Protocol	Supports

Parameter	Details
Video Encoding	H.265A/H.265+/H.265/H.264+/H.264
Video Bitrate	128kbps ~ 8Mbps
Video Streams	Main Stream : 1920 x 1080; 25/30 FPS Sub Stream 1: 720 x 576; 25/30 FPS
Digital Zoom	16X
Audio Input	Yes; 1Ch; 2Vp-p 1k Ω Impedence
Audio Output	Yes; 1Ch; 16 Ω Impedence
Audio Compression	G.711
Image Setup	Mirror Image/Reverse/Color Settings
Alarm	N/A
Intelligent AI Feature	Face Detection; Trip Wire
Operation Temperature	-10 $^{\circ}$ C ~ +55 $^{\circ}$ C
Operation Humidity	0% ~ 90%
Power Supply	DC12V, PoE (IEEE802.3af)(Class 0)
Power Consumption	\leq 8.5W
Dimensions	180mm x 70mm x 70mm
Weight	\leq 0.5 KGs
Ingress Protection	IP67
Certifications	CE, FCC, RoHS.