



SECURUS SS-NC15DXLP-SEF-M3

3.0 MP AI Network Dome Camera

Securus Latest Range of AI Cameras with Face Detection Feature. 3.0 Megapixel Network Dome Camera. It will work on all major DVR. It supports PoE Function. It comes with a weather-proof connector which is ideal for Outdoor Applications.

SECURUS AI Network Camera Range
01-01-2021

H.265AI

3MP

AI


POE

IP67

WDR



**FACE
RECOGNITION**



**ARTIFICIAL
INTELLIGENCE**

Parameter	Details
Model	SS-NC15DXLP-SEF-M3
Make	SECURUS
Image Sensor	1/2.7" Progressive Scan CMOS
Image Pixels	2304 x 1296 Pixels (3.0 MP)
Minimum Illumination	0.01Lux @ (F1.2,AGC ON),0Lux with IR
Day/Night	Auto (ICR) / Color / Black & White
WDR (Wide Dynamic Range)	≥120db
IR LED	2Pcs IR LED
IR LED Technology	SmartEXIR [®] Technology
IR Distance	20~30 Meters
Shutter Type	Manual/Auto
Shutter Speed	1/25s ~ 1/100000s
Lens Mount	3.6/4.0mm
Lens Type	Board Lens
Network Interface	10/100 MBPS RJ45 Connector
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
Electronic Shutter Speed	Manual/Auto (1/25 ~ 1/100000 S)

Parameter	Details
Video Encoding	H.265A/H.265+/H.265/H.264+/H.264
Video Bitrate	128kbps ~ 8Mbps
Video Streams	Main Stream : 2304 x 1296; 1920 x 1080; 25/30 FPS Sub Stream 1: 720 x 576; 25/30 FPS
Digital Zoom	16X
Image Setup	Mirror Image/Reverse/Color Settings
Alarm	N/A
Intelligent AI Feature	Face Detection; Trip Wire
Operation Temperature	-10°C ~ +55°C
Operation Humidity	0% ~ 90%
Power Supply	DC12V, PoE (IEEE802.3af)(Class 0)
Power Consumption	≤8.5W
Dimensions	180mm x 70mm x 70mm
Weight	≤0.5 KGs
Ingress Protection	IP67
Certifications	CE, FCC, RoHS