



SECURUS SS-NC20L2XP-CSF-M3

3.0 MP AI Outdoor Network Bullet Camera

Securus Latest Range of AI Cameras with Face Detection Feature. 3.0 Megapixel Network Bullet Camera. It will work on all major NVR/HVR. It supports PoE Function. It comes with a weather-proof connector which is ideal for Outdoor Applications.

SECURUS AI Network Camera Range
01-01-2021

H.265AI

3.0MP

AI


POE

IP67

WDR



**FACE
RECOGNITION**



**ARTIFICIAL
INTELLIGENCE**

Parameter	Details
Model	SS-NC20L2XP-CSF-M3
Make	SECURUS
Image Sensor	1/2.7" Progressive Scan CMOS
Image Pixels	2304 x 1296 Pixels (3.0 MP)
Minimum Illumination	0.01Lux @ (F1.2,AGC ON),0Lux with IR
Day/Night	Auto (ICR) / Color / Black & White
WDR (Wide Dynamic Range)	≥120db
IR LED	2Pcs White LED
LED Technology	Colorsense [®] Technology
IR Distance	20 ~ 30 Meters
Shutter Type	Manual/Auto
Shutter Speed	1/25s ~ 1/100000s
Lens Mount	3.6/4.0 mm
Lens Type	Board Lens
Network Interface	10/100 MBPS RJ45 Connector
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
Electronic Shutter Speed	Manual/Auto (1/25 ~ 1/100000 S)

Parameter	Details
Video Encoding	H.265A1/H.265+/H.265/H.264+/H.264
Video Bitrate	128kbps ~ 8Mbps
Video Streams	Main Stream : 2304 x 1296; 1920 x 1080; 25/30 FPS Sub Stream 1: 720 x 576; 25/30 FPS
Digital Zoom	16X
Audio	N/A
Audio Compression	N/A
Image Setup	Mirror Image/Reverse/Color Settings
Alarm	N/A
Intelligent AI Feature	Face Detection; Trip Wire
Operation Temperature	-10°C ~ +55°C
Operation Humidity	0% ~ 90%
Power Supply	DC12V, PoE (IEEE802.3af)(Class 0)
Power Consumption	≤8.5W
Dimensions	180mm x 70mm x 70mm
Weight	≤0.5 KGs
Ingress Protection	IP67
Certifications	CE, FCC, RoHS