


## SS-NC20L2XP-SDF-M5(S) | 5.0 MP AI Network Bullet Camera



### Key Features

- Progressive Scan CMOS Sensor.
- Built-in Audio.
- Face Detection & Vehicle Detection Feature.
- Ingress Protection IP67.
- Video Encoding H.265AI/H.265+.



| Parameter                | Details  |
|--------------------------|--|
| Model                    | SS-NC20L2XP-SDF-M5(S)  |
| Make                     | <b>SECURUS</b>   |
| Image Sensor             | 1/2.7" Progressive Scan CMOS   |
| Image Pixels             | 2592 x 1944 Pixels (5.0 MP)  |
| Minimum Illumination     | Color: 0.005Lux@F1.2; B/W: 0.001Lux@F1.2   |
| Day/Night                | Auto (ICR) / Color / Black & White   |
| WDR (Wide Dynamic Range) | ≤140db   |
| IR LED                   | 2Pcs IR LED  |
| IR LED Technology        | SmartEXIR <sup>®</sup> Technology  |
| IR Distance              | 20 ~ 40 Meters   |
| Shutter Type             | Manual/Auto  |
| Shutter Speed            | 1/25s ~ 1/100000s  |
| Lens Mount               | 2.8mm/3.6mm/4.0mm/6.0mm  |
| Lens Type                | Board Lens   |
| Network Interface        | 10/100 MBPS RJ45 Connector   |
| Network Protocol         | HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP |

| Parameter               | Details   |
|-------------------------|---|
| Video Encoding          | H.265A1/H.265+/H.265/H.264+/H.264   |
| Video Bitrate           | 128kbps ~ 8Mbps   |
| Video Streams           | Triple Stream   |
| Video Stream Resolution | Max : 2592 x 1944; 1920 x 1080; 720 x 576;<br>25/30 FPS   |
| Digital Zoom            | Supported (Max: 16X)  |
| Audio Input             | Yes; 1Ch; 2Vp-p 1k $\Omega$ Impedence   |
| Audio Output            | Yes; 1Ch; 16 $\Omega$ Impedence   |
| Audio Compression       | G.711   |
| Image Setup             | Mirror Image/Reverse/Color Settings   |
| Alarm                   | N/A   |
| Intelligent AI Feature  | Face Detection, Vehicle Detection,<br>Human Detection, Active Deterrence,<br>Line Crossing, Trip Wire |
| Operation Temperature   | -10°C ~ +65°C   |
| Operation Humidity      | 0% ~ 90%  |
| Power Supply            | DC12V, PoE (IEEE802.3af)(Class 0)   |
| Power Consumption       | ≤3.6W without IR; ≤6W with IR   |
| Multiple Browsers       | Supports (Chrome, Mozilla, Edge, Opera)   |

| Parameter          | Details                           |
|--------------------|-----------------------------------|
| SD Card            | Supported (Max: 512GB) (Optional) |
| Housing Material   | Aluminium + ABS                   |
| Dimensions         | 180mm x 70mm x 70mm               |
| Weight             | ≤0.5 KGs                          |
| Ingress Protection | IP67                              |
| Certifications     | CE, FCC, RoHS, BIS                |