



## **SECURUS SS-NC20L2XP-SEF-M3**

3.0 MP AI Outdoor Network Bullet Camera

Securus Latest Range of AI Cameras with Face Detection & Face Recognition Feature. 3.0 Megapixel Network Bullet Camera. It will work on all major NVR/HVR. It supports PoE Function. It comes with a weather-proof connector which is ideal for Outdoor Applications.

SECURUS AI Network Camera Range  
01-01-2021

**H.265AI**

**3MP**

**AI**


**POE**

**IP67**

**WDR**



**FACE  
RECOGNITION**



Parameter	Details
Model	SS-NC20L2XP-SEF-M3
Make	<b>SECURUS</b>
Image Sensor	1/2.7" Progressive Scan CMOS
Image Pixels	2304 x 1296 Pixels (3.0 MP)
Minimum Illumination	0.01Lux @ (F1.2,AGC ON),0Lux with IR
Day/Night	Auto (ICR) / Color / Black & White
WDR (Wide Dynamic Range)	≥120db
IR LED	2Pcs IR LED
IR LED Technology	SmartEXIR <sup>®</sup> Technology
IR Distance	20~30 Meters
Shutter Type	Manual/Auto
Shutter Speed	1/25s ~ 1/100000s
Lens Mount	3.6/4.0mm
Lens Type	Board Lens
Network Interface	10/100 MBPS RJ45 Connector
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
Electronic Shutter Speed	Manual/Auto (1/25 ~ 1/100000 S)

Parameter	Details
<b>Video Encoding</b>	H.265A1/H.265+/H.265/H.264+/H.264
<b>Video Bitrate</b>	128kbps ~ 8Mbps
<b>Video Streams</b>	Main Stream : 2304 x 1296; 1920 x 1080 25/30 FPS Sub Stream 1: 720 x 576; 25/30 FPS
<b>Digital Zoom</b>	16X
<b>Image Setup</b>	Mirror Image/Reverse/Color Settings
<b>Alarm</b>	N/A
<b>Intelligent AI Feature</b>	Face Detection; Trip Wire
<b>Operation Temperature</b>	-10°C ~ +55°C
<b>Operation Humidity</b>	0% ~ 90%
<b>Power Supply</b>	DC12V, PoE (IEEE802.3af)(Class 0)
<b>Power Consumption</b>	≤8.5W
<b>Dimensions</b>	180mm x 70mm x 70mm
<b>Weight</b>	≤0.5 KGs
<b>Ingress Protection</b>	IP67
<b>Certifications</b>	CE, FCC, RoHS