



## **SECURUS SS-NE12XS-M2**

2.0 Megapixel Outdoor 12X IP Speed Dome Camera.

A Professional 12X 2.0 Megapixel Outdoor Network Speed Dome Camera which supports Edge Storage function which makes sure you store data even when not connected to NVR. It is **ONVIF** Compliant which means that it will work on all major NVR/HVR. Supports Mobile Viewing on iPhone and Android. It supports Micro SD Card, Alarm and BNC Output (Optional). The IR Range for this model is 60 Meters.

**SECURUS IPC PTZ RANGE**  
**1-4-2016**

**2.0MP**

**12X**

**Audio**

**DC12v**

**60M**

**IP66**

Parameter	Details
<b>Model</b>	SS-NE12XS-M2
<b>Make</b>	<b>SECURUS</b>
<b>Image Sensor</b>	1/3", 2.0 Megapixel, progressive scan, CMOS
<b>Lens</b>	5.1mm ~ 61.0 mm (12x optical zoom)
<b>Iris</b>	Auto/Manual; F1.6 ~ F1.8
<b>Shutter</b>	Auto/Manual.
<b>Shutter Time</b>	1/6s ~ 1/8000s
<b>Minimum Illumination</b>	Color: 0.03 Lux B/W: 0.01 Lux (IR ON: 0.0 Lux)
<b>S/N Ratio</b>	≥ 50dB
<b>Day/Night Mode</b>	IR-Cut filter with auto switch (ICR)
<b>IR Distance</b>	60 Meters
<b>IR LEDs</b>	6Pcs 42Mil Array LED
<b>Audio Input</b>	Supports built-in Audio (Optional)
<b>Video Compression</b>	H.264
<b>Video Resolution</b>	1920 x 1080 Pixels (Max)
<b>CVBS Output</b>	Supports 1 x BNC Video Output (Optional)
<b>Frame Rate</b>	1080P @ 30FPS; 720P @ 30FPS; D1 @ 25FPS
<b>Video Streaming</b>	Triple Streams
<b>OSD</b>	Up to 8 OSDs
<b>Privacy Mask</b>	Up to 8 Areas
<b>Digital Zoom</b>	Supports

Parameter	Details
<b>SD Card</b>	Optional (Micro SD Card) (Max: 32GB)
<b>Alarm I/O</b>	1 / 1 (Optional)
<b>Network Protocols</b>	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, QOS, NTP, FTP, HTTP, SNMP, SIP
<b>DDNS</b>	<a href="http://www.securusddns.com">www.securusddns.com</a> (Free DDNS)
<b>Compliance</b>	ONVIF
<b>Pan Range</b>	360° Endless
<b>Pan Speed</b>	0.02°/s ~ 45°/s
<b>Tilt Range</b>	-15° ~ +90° (Auto-Reverse)
<b>Tilt Speed</b>	0.1°/s ~ 30°/s
<b>Auto Flip</b>	Pan: 180°; Tilt: 93°
<b>Presets</b>	220 Presets
<b>Dwell Time</b>	1s ~ 60s Selectable
<b>Guard Tours</b>	3 Tours
<b>Guard Points</b>	Max: 16 Points
<b>Communication Protocol</b>	Pelco-D; Pelco-P
<b>Baud Rate</b>	9600BPS (Default)
<b>Park Time</b>	1 ~ 60 Minutes
<b>Network</b>	10M/100M Base-TX Ethernet
<b>Power Supply</b>	12V 3Amp
<b>Power Consumption</b>	~ 15W (Without IR)

<b>Parameter</b>	<b>Details</b>
<b>Weight</b>	2.48 KGs
<b>Working Temperature</b>	-40°C ~ +65°C
<b>Working Humidity</b>	≤90% RH (Non Condensing)
<b>Ingress Protection</b>	IP66
<b>Lightning Protection</b>	Transient Voltage 6000V