SECURUS®
Security. Never Compromise!!

ONVIF PROTOCOL IP CAMERA

SECURUS SS-NE15XS-M2

2.0 Megapixel Outdoor 15X IP Speed Dome Camera.

A Professional 15X 2.0 Megapixel Outdoor Network Speed Dome Camera which supports Edge Storage function which makes sure you store data even when not connected to NVR. It is ONVIF Compliant which means that it will work on all major NVR/HVR. Supports Mobile Viewing on iPhone and Android. It supports Micro SD Card, Alarm and BNC Output (Optional). The IR Range for this model is 60 Meters.

SECURUS IP PTZ CAMERA RANGE
01-04-2016

2.0MP	15X	ONVIF
DC12V	60 M	IP66

© K. M. Electronic Cables Pvt. Ltd. - Ahmedabad. All Rights Reserved.
Specifications are subject to change without prior notice.

SECURUS®
Security. Never Compromise!!

Parameter	Details
Model	SS-NE15XS-M2
Make	SECURUS
Image Sensor	1/3”, 2.0 Megapixel, progressive scan, CMOS
Lens	5.0mm ~ 75.0 mm (15x optical zoom)
Iris	Auto/Manual; F1.6 ~ F4.8
Shutter	Auto/Manual.
Shutter Time	1/6s ~ 1/8000s
Minimum Illumination	Color: 0.03 Lux B/W: 0.01 Lux (IR ON: 0.0 Lux)
S/N Ratio	≥ 50dB
Day/Night Mode	IR-Cut filter with auto switch (ICR)
IR Distance	60 Meters
Audio Compression	G.711
Audio Input	Supports built-in Audio (Optional)
Video Compression	H.265+, H.265, H.264
Video Resolution	1920 x 1080 Pixels (Max)
CVBS Output	Supports 1 x BNC Video Output (Optional)
Frame Rate	1080P @ 20FPS; 720P @ 30FPS; D1 @ 25FPS
Video Streaming	Triple Streams

© K. M. Electronic Cables Pvt. Ltd. - Ahmedabad. All Rights Reserved.
Specifications are subject to change without prior notice.

SECURUS®
Security. Never Compromise!!

Parameter	Details
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 Areas
Digital Zoom	Supports
Alarm I/O	1/1 (Optional)
Network Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, QOS, NTP, FTP, HTTP, SNMP, SIP
Compliance	ONVIF
Pan Range	360° Endless
Pan Speed	0.02°/s ~ 80°/s
Tilt Range	0° ~ +90° (Auto-Reverse)
Tilt Speed	0.1°/s ~ 40°/s
Auto Flip	Pan: 180°; Tilt: 93°
Presets	220 Presets
Dwell Time	1s ~ 60s Selectable
Guard Tours	3 Tours
Guard Points	Max: 16 Points
Communication Protocol	Pelco-D; Pelco-P
Baud Rate	9600BPS (Defaut)

© K. M. Electronic Cables Pvt. Ltd. - Ahmedabad. All Rights Reserved.
Specifications are subject to change without prior notice.

SECURUS®
Security. Never Compromise!!

Parameter	Details
Park Time	1 ~ 60 Minutes
Network	10M/100M Base-TX Ethernet
Power Supply	12V 4Amp
Power Consumption	~ 25W (Without IR)
Weight	5.28 KGs
Working Temperature	-40°C ~ +65°C
Working Humidity	≤90% RH (Non Condensing)
Ingress Protection	IP66
Lightning Protection	Transient Voltage 6000V
Certifications	CE, FCC

© K. M. Electronic Cables Pvt. Ltd. - Ahmedabad. All Rights Reserved.
Specifications are subject to change without prior notice.