



SECURUS SS-NE20L2P-M4

4.0 Megapixel Outdoor IP Bullet Camera with PoE

A Professional 4.0 Megapixel IP Camera Bullet. It is **ONVIF** Compliant which means that it will work on all major NVR/HVR. It supports PoE Function. It comes with a weather-proof connector which is ideal for Outdoor Applications.



SPECIAL FEATURE



Conventional



Wide Dynamic Range (WDR)



WEATHERPROOF
RJ45 CONNECTOR

Parameter	Details
Model	SS-NE20L2P-M4
Make	SECURUS
Image Sensor	4.0MP Progressive Scan CMOS
Image Pixels	2592 x 1520 Pixels (4.0 MP)
Minimum Illumination	0.01Lux @(F1.2,AGC ON),0Lux with IR
Day/Night	Auto (ICR) / Color / Black & White
WDR (Wide Dynamic Range)	≥80db
IR LEDs	24 IR LEDs
IR Distance	20 ~ 40 Meters
Lens Mount	3.6mm/6.0mm Megapixel Board Lens
Network Interface	10/100 MBPS RJ45 Connector
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
Electronic Shutter Speed	Manual/Auto (1/25 ~ 1/100000 S)
DDNS Service	FREE DDNS: www.securusddns.com
ONVIF Protocol	Supports
Video Encoding	H.264
Video Bitrate	128kbps ~ 8Mbps
Video Streams	Main Stream : 2592 x 1520; 30 FPS Sub Stream 1: 720 x 576; 30 FPS

Parameter	Details
Audio Input	Yes
Audio Output	Yes
Audio Compression	PCMV/PCMA
Audio Bitrate	64Kbps(G.711) / 16Kpbs(G.726)
Image Setup	Mirror Image/Reverse/Color Settings
Alarm	Motion Detection
Alarm I/O	N.A.
Operation Temperature	-10°C ~ +55°C
Operation Humidity	0% ~ 90%
Power Supply	DC12V / 2Amperes
PoE (Power Over Ethernet)	PoE (IEEE802.3af)
IP Rating	IP66
Power Consumption	≤3.5W (Without IR)
Weight	≤1.0 KGs (No HDD)

