



SECURUS SS-NE20XS-M2

2.0 Megapixel Outdoor 20X IP Speed Dome Camera.

A Professional 20X 2.0 Megapixel Outdoor Network Speed Dome Camera which supports Edge Storage function which makes sure you store data even when not connected to NVR. It is **ONVIF** Compliant which means that it will work on all major NVR/HVR. Supports Mobile Viewing on iPhone and Android. It supports Micro SD Card, Alarm and BNC Output (Optional). The IR Range for this model is 120 Meters.

SECURUS IPC PTZ RANGE
1-4-2016

2.0MP

20X

Audio

DC12v

120M

IP66

| Parameter | Details |
|-----------------------------|---|
| Model | SS-NE20XS-M2 |
| Make | SECURUS |
| Image Sensor | 1/3", 2.0 Megapixel, progressive scan, CMOS |
| Lens | 4.7mm ~ 94.0 mm (20x optical zoom) |
| Iris | Auto/Manual; F1.6 ~ F2.8 |
| Shutter | Auto/Manual. |
| Shutter Time | 1/6s ~ 1/8000s |
| Minimum Illumination | Color: 0.03 Lux B/W: 0.01 Lux (IR ON: 0.0 Lux) |
| S/N Ratio | ≥ 50dB |
| Day/Night Mode | IR-Cut filter with auto switch (ICR) |
| IR Distance | 120 Meters |
| Audio Compression | G.711 |
| Audio Input | Supports built-in Audio (Optional) |
| Video Compression | H.264 |
| Video Resolution | 1920 x 1080 Pixels (Max) |
| CVBS Output | Supports 1 x BNC Video Output (Optional) |
| Frame Rate | 1080P @ 30FPS; 720P @ 30FPS; D1 @ 25FPS |
| Video Streaming | Triple Streams |
| OSD | Up to 8 OSDs |
| Privacy Mask | Up to 8 Areas |
| Digital Zoom | Supports |

| Parameter | Details |
|-------------------------------|---|
| SD Card | Optional (Micro SD Card) (Max: 32GB) |
| Alarm I/O | 1 / 1 (Optional) |
| Network Protocols | L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, QOS, NTP, FTP, HTTP, SNMP, SIP |
| DDNS | www.securusddns.com (Free DDNS) |
| Compliance | ONVIF |
| Pan Range | 360° Endless |
| Pan Speed | 0.02°/s ~ 120°/s |
| Tilt Range | -15° ~ +90° (Auto-Reverse) |
| Tilt Speed | 0.1°/s ~ 160°/s |
| Auto Flip | Pan: 180°; Tilt: 93° |
| Presets | 220 Presets |
| Dwell Time | 1s ~ 60s Selectable |
| Guard Tours | 3 Tours |
| Guard Points | Max: 16 Points |
| Communication Protocol | Pelco-D; Pelco-P |
| Baud Rate | 9600BPS (Default) |
| Park Time | 1 ~ 60 Minutes |
| Network | 10M/100M Base-TX Ethernet |
| Power Supply | 12V 4Amp |
| Power Consumption | ~ 25W (Without IR) |

| Parameter | Details |
|-----------------------------|--------------------------|
| Weight | 5.28 KGs |
| Working Temperature | -40°C ~ +65°C |
| Working Humidity | ≤90% RH (Non Condensing) |
| Ingress Protection | IP66 |
| Lightning Protection | Transient Voltage 6000V |