


SS-NE36XS-M2 | 2.0 MP Outdoor 36X IP Speed Dome Camera



Key Features

- Progressive Scan CMOS Sensor.
- Face Detection.
- ONVIF Conformant.
- Video Encoding H.265AI/H.265+.
- Mobile Viewing on iPhone and Android.



Parameter	Details
Model	SS-NE36XS-M2
Make	SECURUS
Image Sensor	1/2.8", 2.0 Megapixel, progressive scan, CMOS
Lens	4.6mm ~ 165 mm (36x optical zoom)
Iris	Auto/Manual; F1.6 ~ F4.8
Shutter	Auto/Manual.
Shutter Time	1/6s ~ 1/8000s
Minimum Illumination	Color: 0.03 Lux B/W: 0.01 Lux (IR ON: 0.0 Lux)
S/N Ratio	≥ 50dB
Day/Night Mode	IR-Cut filter with auto switch (ICR)
IR Distance	250 Meters
Audio Compression	G.711
Audio Input	Supports built-in Audio (Optional)
Video Compression	H.265+, H.265, H.264
Video Resolution	1920 x 1080 Pixels (Max)
CVBS Output	Supports 1 x BNC Video Output (Optional)
Frame Rate	1080P @ 30FPS; 720P @ 30FPS; D1 @ 25FPS

Parameter	Details
Video Streaming	Triple Streams
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 Areas
Digital Zoom	Supports
Alarm I/O	1/1 (Optional)
Network Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, QOS, NTP, FTP, HTTP, SNMP, SIP
Compliance	ONVIF
Pan Range	360° Endless
Pan Speed	0.02°/s ~ 200°/s
Tilt Range	-15° ~ +90° (Auto-Reverse)
Tilt Speed	0.1°/s ~ 160°/s
Auto Flip	Pan: 240°; Tilt: 180°
Presets	220/500 Presets
Dwell Time	1s ~ 60s Selectable
Guard Tours	3 Tours
Guard Points	Max: 16 Points
Communication Protocol	Pelco-D; Pelco-P

Parameter	Details
Baud Rate	9600BPS (Default)
Intelligent AI Feature	Face Detection; Trip Wire
Park Time	1 ~ 60 Minutes
SD Card	Supported (Max: 512 GB) (Optional)
Network	10M/100M Base-TX Ethernet
Power Supply	12V 4Amp
Power Consumption	~ 25W (Without IR)
Multiple Browsers	Supports(Chrome,Mozilla,Edge,Opera)
Housing Material	Aluminum + ABS
Weight	5.28 KGs
Working Temperature	-40°C ~ +65°C
Working Humidity	≤90% RH (Non Condensing)
Ingress Protection	IP67
Lightning Protection	Transient Voltage 6000V
Certifications	CE, FCC, RoHS, BIS