



## **SECURUS SS-NE6XS-M2**

2.0 Megapixel Outdoor 6X IP Speed Dome Camera.

A Professional 6X 2.0 Megapixel Outdoor Network Speed Dome Camera which is a Vandalproof IK10 Rating Camera. It will work on all major NVR/HVR. Supports Mobile Viewing on iPhone and Android. It supports Micro SD Card, Alarm and BNC Output (Optional). The IR Range for this model is 45 Meters.

SECURUS IP PTZ CAMERA RANGE

01-04-2018

**2.0MP**

**6X**

**Audio**

**DC12V**

**45 M**

**IP66**

Parameter	Details
Model	SS-NE6XS-M2
Make	<b>SECURUS</b>
Image Sensor	1/3", 2.0 Megapixel, progressive scan, CMOS
Lens	2.8mm ~ 16.8 mm (6x optical zoom)
Iris	Auto/Manual; F1.6 ~ F4.8
Shutter	Auto/Manual.
Shutter Time	1/6s ~ 1/8000s
Minimum Illumination	Color: 0.03 Lux B/W: 0.01 Lux (IR ON: 0.0 Lux)
S/N Ratio	≥ 50dB
Day/Night Mode	IR-Cut filter with auto switch (ICR)
IR Distance	45 Meters
Audio Compression	G.711, PCM
Audio Input	Supports built-in Audio (Optional)
Video Compression	H.264, H.265
Video Resolution	1920 x 1080 Pixels (Max)
CVBS Output	Supports 1 x BNC Video Output (Optional)
Frame Rate	1080P @ 20FPS; 720P @ 30FPS; D1 @ 25FPS
Video Streaming	Triple Streams

Parameter	Details
<b>OSD</b>	Up to 8 OSDs
<b>Privacy Mask</b>	Up to 8 Areas
<b>Digital Zoom</b>	Supports
<b>Alarm I/O</b>	1/1 (Optional)
<b>Network Protocols</b>	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, QOS, NTP, FTP, HTTP, SNMP, SIP
<b>Pan Range</b>	0 ~ 355°
<b>Pan Speed</b>	0.02°/s ~ 25°/s
<b>Tilt Range</b>	-0° ~ +70° (Auto-Reverse)
<b>Tilt Speed</b>	0.1°/s ~ 20°/s
<b>AB Scan Speed</b>	1 ~ 9 Grades
<b>Presets</b>	220 Presets
<b>Dwell Time</b>	1s ~ 60s Selectable
<b>Guard Tours</b>	3 Tours
<b>Guard Points</b>	Max: 16 Points
<b>Communication Protocol</b>	Pelco-D; Pelco-P
<b>Baud Rate</b>	9600BPS (Default)

Parameter	Details
<b>Park Time</b>	1 ~ 60 Minutes
<b>Network</b>	10M/100M Base-TX Ethernet
<b>Power Supply</b>	12V 4Amp
<b>Power Consumption</b>	~ 25W (Without IR)
<b>Weight</b>	5.28 KGs
<b>Working Temperature</b>	-40°C ~ +65°C
<b>Working Humidity</b>	≤90% RH (Non Condensing)
<b>Ingress Protection</b>	IP66
<b>Lightning Protection</b>	Transient Voltage 3000V