


**SS-20L2XG-CSUTL-M3(SM)/SL** | 3.0 MP 4G Camera. Compatible with 5G Sim Card



## Key Features

- Progressive Scan CMOS Sensor.
- Mobile Phone Monitoring (iOS, Android).
- Human & Sound Detection.
- Ingress Protection IP67.
- Video Encoding H.265X.



Parameter	Details
Model	SS-20L2XG-CSUTL-M3(SM)/SL
Make	SECURUS
Image Sensor	1/2.9" Progressive Scan CMOS
Image Pixels	2304 x 1296 Pixels (3.0MP)
Minimum Illumination	Color: 0.005Lux@F1.2; B/W: 0.001Lux@F1.2
Day/Night	Auto (ICR) / Color / Black & White
DWDR	Auto
BLC (Back Light Compensation)	On/Off
Night Vision	1Pcs Warm Light LED; 2Pcs Strobe LED
Night Light Temperature	3000~3300K
Night Vision Technology	Colorsense <sup>®</sup> Technology
Night Vision Distance	20 Meters
Lens Mount	2.8mm/3.6mm
Lens Type	Board Lens
Network Type	4G (Compatible with 5G Sim Card)
4G Standard	LTE-TDD/LTE-FDD/TD-SCDMA/ WCDMA
4G Frequency Band	LTE-FDD : B1/B3/B5/B8, LTE-TDD : B34/B38/B39/B40/B41; WCDMA:B1/B5/B8

Parameter	Details
Network Interface	10/100 MBPS RJ45 Connector
Network Protocol	HTTP, TCP, ARP, RTMP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
ONVIF Protocol	Supported (Ethernet Port Only)
SD Card	Supported (Max: 256 GB)
Video Bitrate	128kbps ~ 8Mbps
Video Compression	H.265X, H.264
Video Streams	HD/SD, Rate Adaptation, Triple Stream
Image Resolution	Mainstream: 2304*1296, 1920*1080; Auxiliary stream: 1280*720, 704*576, 640*480, 352*288 Snapstream: 704*576, 640*480, 352*288
Frame Rate	1296P @ 15FPS; 1080P @ 15FPS; 720P @ 15FPS; D1 @ 15FPS
DNR	2DNR, 3DNR (Digital Noise Reduction)
Shutter Speed	1/25s ~ 1/100000s (Shutter Adaptation)
Digital Zoom	Supported (Max: 16X)
Audio Input	Yes; (Built-in Mic)
Audio Output	Yes; (Built-in Speaker)
Audio Compression	G.711A

Parameter	Details
Intelligent AI Feature	Human Detection, Sound Detection
Alarm Notification	Push Notification on Mobile Application
Image reversal	Vertical Flip / Horizontal Mirror
Privacy Mask	Up to 4 Areas
Antenna	Dual Antenna
Antenna Frequency Range	824-960MHz, 1710-2690MHz
Antenna Impedance	50Ω
Antenna VSWR	≤3.0
Antenna Gain	3dBi
Antenna Bandwidth	136/980MHz
Housing Material	Aluminium + ABS
Weight	≤0.5 KGs
Dimension	80W X 143L X 128.5H
Operation Temperature	-10°C ~ +65°C
Operation Humidity	0% ~ 90%
Power Supply	DC12V
Power Consumption	≤5W
Ingress Protection	IP67

Parameter	Details
Mobile Application	PVMS Pro 4K
Mobile OS	Android, iOS
Browsers Supported	Chrome, Edge, Opera, Mozilla Firefox
Certifications	CE, FCC, RoHS

## Securus Overview

Securus CCTV is one of the Largest Indian Manufacturer & Supplier of Video Surveillance Products like High Definition Cameras, Standalone Recorders, Network Recorders, POE Switches, Video Management Surveillance Software, CCTV & Networking Cables for Surveillance & Other Surveillance Products & Solutions. Powered by In House R&D Team & State-of-the Art Factory in Electronic Zone Gandhinagar. We Manufacture Products under the **Make in India** Initiative.



## Securus AI Technology



### Head Office

K.M. ELECTRONIC CABLES PRIVATE LIMITED  
"K.M. House", Near C.U. Shah College,  
Ahmedabad, Gujarat-380014

### Factory

K.M. ELECTRONIC CABLES PRIVATE LIMITED  
B-20, GIDC Electronics Estate, Sector 25,  
Gandhinagar, Gujarat-382024

### Email

sales@securusctv.com

### Securus Helpline

85911 85511

### Securus Website

[www.securusctv.com](http://www.securusctv.com)