


SS-N8032RV-H4-M5 | AI Network Video Recorder



Key Features

- Playback and Backup modes.
- ONVIF Support.
- Face Detection & Vehicle Detection.
- RMEye Pro Mobile Application.
- Video Compression H.265AI/H.265+.



Parameter	Details
Model	SS-N8032RV-H4-M5
Make	SECURUS
User Interface	Graphic User Interface (GUI)
Operating System	Embedded Linux
Operation Mode	Preview, Record, Playback, Backup, Network, Smart Search
Playback Mode	Common Playback, Smart Search
Password Security	Multi-level User Management
ONVIF	Support
Video Input	32ch 5M/32ch1080P/8ch4K
HDMI Output	Supports (Max : 4K)
VGA Output	Supports (Max : 1080P)
CVBS main output	N.A.
Audio Input	1 Ch
Audio output	1 Ch, RCA connector
Display	1/4/6/8/9/10/13/16/25/32 optional
Video standard	PAL/NTSC
Video compression	H.265AI/H.265+/H.265/H.264+/H.264
Intelligent Functions	Face Detection, Vehicle Detection, Human Detection, Active Deterrence, Line Crossing, Trip Wire, People Counting
Video encoding resolution	12MP; 8MP; 5MP; 4MP; 3MP; 1080P

Parameter	Details
Network Protocol	HTTP, TCP/IP, UDP, DNS/DDNS, RTP, RTSP, DHCP, NTP
Video frame rate	PAL: 1-25 FPS NTSC: 1-30FPS
Video bit rate	1536kbps-3072kbps
Stream Type	Video & Audio/Video
Audio compression	G.711a
Recording mode	Always/Schedule/Alarm Recording/Motion Detection Recording
Video search	Time/Channel/Event/Face Search/Vehicle Search
Display Zoom	Live Playback & Mobile
Audio bit rate	8-32kbps
Dual-stream	Supports
Mobile Monitoring	"RMEye Pro" Application for Android And iPhone
Recording resolution	32 CH Realtime Recording
HDD Port	4 SATA
HDD Maximum Capacity	12TB for each Sata connector
Voice talk	Support; 1CH BNC line in/1CH RCA Audio out.
Record mode	Audio & Video recording simultaneously
Remote control	Supports
Network protocol	Supports IE/PPPoE/DDNS
Multiple IP Network Configuration	Supported

Parameter	Details
Network Bandwidth	240 Mbps Incoming / 240 Mbps Outgoing
DDNS Server	www.securusddns.com
Network	1 RJ45 10M/100M/1000M
NVR to NVR Cascading	Remote, Local, Viewing, Recording
IPC firmware update	Supported
USB Connector	2 x USB2.0, 1 x USB3.0
Firmware update	Support USB update/Network update
Serial Interface	RS485, RS232
Alarm input	16
Alarm output	4
Power supply	NVR: DC 12V 6A
Redundancy	Available
Network Security	Support Blacklist/Whitelist to prevent unauthorized Network Access
Virtual Lan	Configure with Multi IP Addresses
Operation Temperature	-10°C to +65°C
Operation Humidity	10% to 90%
Chassis	Standard 1.5U
Dimension	400.5mm (W) × 440mm (L) × 60mm (H)
Weight(without HDD)	≤1.0Kg
Certifications	CE, FCC, RoHS, BIS

Securus Overview

Securus CCTV is one of the Largest Indian Manufacturer & Supplier of Video Surveillance Products like High Definition Cameras, Standalone Recorders, Network Recorders, POE Switches, Video Management Surveillance Software, CCTV & Networking Cables for Surveillance & Other Surveillance Products & Solutions. Powered by In House R&D Team & State-of-the Art Factory in Electronic Zone Gandhinagar. We Manufacture Products under the **Make in India** Initiative.



Securus AI Technology



Head Office

SECURUS CCTV INDIA PRIVATE LIMITED
"K.M. House", Near C.U. Shah College,
Ahmedabad, Gujarat-380014

Factory

SECURUS CCTV INDIA PRIVATE LIMITED
B-20, GIDC Electronics Estate, Sector 25,
Gandhinagar, Gujarat-382024

Email

sales@securuscttv.com

Securus Helpline

85911 85511

Securus Website

www.securuscttv.com